



POWER

FREQUENCY BIT

Accuphase

LOCKED

LEVEL

0.0

4B

- USB
- OPT 1
- OPT 2
- COAX 1
- COAX 2
- COAX 3
- BAL
- HS-LINK

DOWN

UP

LEVEL

precision MDSD digital processor DC-950

DIGITAL INPUTS

HS-LINK **BALANCED** COAXIAL 3 2 1 OPTICAL 2 1 USB

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE OPERATION.

DIGITAL OUTPUTS

COAXIAL OPTICAL

ANALOG OUTPUTS

LINE **BALANCED** LINE **BALANCED**

RIGHT LEFT

BALANCED CONNECTION

1 GND 1 GND
2 - 2 +
3 + 3 -

Accuphase MODEL DC-950

POWER CONSUMPTION 31W AC230V-50/60Hz

ACCUPHASE LABORATORY, INC. MADE IN JAPAN

2-14-10 SHIRI-SHIKAWA, Aoba-KU, YOKOHAMA, JAPAN

CAUTION
RISK OF ELECTRIC SHOCK
DO NOT OPEN

AVIS: RISQUE DE CHOC ELECTRIQUE - NE PAS OUVRIIR.

SERIAL NO. _____

~ AC IN